

Infineum D1212

Description

Infineum D1212 is a DI package optimised to formulate API CF1 with high TBN2 for mono-grade and multi-grade lubricants using appropriate Group I basestocks. Infineum D1212 can be rationalised to API CD, CC, CB and CA performance levels and combines with Infineum D1222 to provide a cascade system offering mixed gasoline and diesel performance levels, from API CF1/SF to API SB/CA. Guidelines are given below.

Performance Level:	SAE Viscosity Grade:	Mass %:	TBN, nominal:
API CF	15W-40, 20W-40, 20W-50, 10W, 20W, 30, 40, 50	5.0	11.0
API CF	20W, 30, 40, 50	4.73	-
Allison C4			
API CF	20W, 30, 40, 50	5.0	-
Allison C4			
API CD	15W-40, 20W-40, 20W-50, 20W, 10W, 30, 40, 50	4.0	8.8
API CC	20W, 30, 40, 50	2.8	6.0
API CB	20W, 30, 40, 50	2.3	5.0
API CA	20W, 30, 40, 50	2.1	5.0
API SF/CF	15W-40, 20W-40, 25W-50	2.5 + Infineum D1222 at 4.2 %	-
MB-Approval 227.1			
ACEA E1-96			
Allison C4			
API SF/CF	20W, 10W, 30, 40, 50	2.5 + Infineum D1222 at 4.2 %	-
MB-Approval 227.0			
ACEA E1-96			
Allison C4			
API SF/CF	15W-40, 20W-40, 20W-50, 20W, 10W, 30, 40, 50	2.4 + Infineum D1222 at 3.4 %	-
API SF/SE/CD	15W-40, 20W-40, 20W-50, 10W, 20W, 30, 40, 50	1.3 + Infineum D1222 at 3.4 %	-
MAN 270			
API SF/SE/CC	10W-30, 10W	0.0 + Infineum D1222 at 4.9 %	-
API SF/SE/CC	15W-40, 20W-40, 20W-50, 20W, 30, 40, 50	0.0 + Infineum D1222 at 4.1 %	-
API SD/CC	20W, 30, 40, 50	0.8 + Infineum D1222 at 2.2 %	-
API SC/CC	15W-40, 20W-40, 20W-50	1.1 + Infineum D1222 at 1.7 %	-
API SC/CC	20W, 30, 40, 50	1.2 + Infineum D1222 at 1.5 %	-
API SB/CB	20W, 30, 40, 50	0.6 + Infineum D1222 at 1.1 %	-
API SB/CA	20W, 30, 40, 50	0.0 + Infineum D1222 at 1.3 %	-

API OF bala is built incensione in selected Group Follows.
TBN can be raised to 13 mg KOH/g via uptreats or using Infineum C9340 as TBN booster.

Typical Inspections

Property:	Value ^(a) :	Unit:	Method ^(b) :
Appearance	Brown Viscous Liquid		Visual inspection
Base Number	221	mg KOH/g	ASTM D2896
Boron	0.05	%(m)	ASTM D5185
Density @ 15 C, kg/m3	1030	kg/m3	ASTM D4052

Version: 4 March 2013 (2.0)

The information contained in this document is based upon data balaves to be reliable at the data of this version and relates only to the matters specifically mentioned in this document. Although Infineum has used reasonable skill and care in the preparation of this information, in the absence of any overriding abligations arising under a specific cathotic, no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information, rolting in this document shall reduce the user's responsibility to stativity itself as to the suitability. Accuracy, reliability and completeness of such information for the particular use; there are exponsibility to stativity itself as to the suitability. Accuracy, reliability and completeness of such information for the particular use; there are exponsibility to stativity itself as to the suitability. Accuracy, reliability and completeness of the information rolting in this document is a partice cathotic on plays damage or injury that may occur from the use of this information on ther than death or personal injury caused by its negligence. Before use of information contained in this information and the information on the subsective containes with information.

Infineum', Dobanax', Paratac', Synacto', Vektron', Vistone' and the corporate mark comprising the interlocking ripple device are trademarks of Infineum International Limited.

© Copyright INFINEUM INTERNATIONAL LIMITED (2013). All rights reserved.

Flash Point Deg C	110 Minimum	C	ASTM D93
Kinematic Viscosity @ 100 C	73	cSt	ASTM D445
Kinematic Viscosity @ 40 C	1122	cSt	ASTM D445
Magnesium	4.83	%(m)	ASTM D5185
Mineral Oil	47	%(m)	Calculated
Nitrogen	0.42	%(m)	ASTM D5291
Phosphorus	1.15	%(m)	ASTM D4927
Sulfated Ash	26.0	%(m)	Calculated
Zinc	1.26	%(m)	ASTM D4927

(a)Not a specification, (b)Methods typically used by Infineum manufacturing plants

Handling / Precautions

Follow precautions normally taken for handling lube oil stocks. This product is temperature sensitive. Do not heat over the maximum loading / unloading temperature to avoid possible release of extremely odorous alkyl mercaptans and/or toxic hydrogen sulfide.

Localized high temperatures should be avoided during heating, especially when product cannot be agitated. Electrical, steam or hot oil heating systems with a self limiting maximum temperature not exceeding 120 Deg. C/250 Deg. F (e.g. low pressure steam at 2 bar(g) or 30 psig) are recommended.

It is strongly recommended that for long term storage the temperature should not exceed 50 °C.

Min Load/Unload Temp:	40 ℃ (104 ° F)
Max Load/Unload Temp:	50 ℃ (122 ° F)
Vis @ Min Load/Unload Temp:	1,120 cSt
Vis @ Max Load/Unload Temp:	620 cSt
Maximum Storage Temperature:	45 ℃ (113 ° F)
Do not reheat above:	50 ℃ (122 ° F)

For detailed data please refer to the relevant MSDS.

Further Information

For further information please contact your local Infineum affiliate or representative.

Version: 4 March 2013 (2.0)

The information contained in this document is based upon data believed to be reliable at the date of this version and relates only to the matters specifically mentioned in this document. Although Infineum has used reasonable skill and care in the preparation of this information, in the absence of any overriding obligations arising under a specific contract, no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information, rothing in this document shall reduce the user's responsibility to statily subtability, accuracy, reliability, and completeness of such information for its particular use; there is warranty against intellectual property infringement; and infineum shall not be lable for any lass, damage or injury that may occur from the use of this information on the previous with infineum.

Infineum', Dobanax', 'Paratac', 'Synacto', Vektron', 'Vistone' and the corporate mark comprising the interlocking ripple device are trademarks of infineum International Limited.

© Copyright INFINEUM INTERNATIONAL LIMITED (2013). All rights reserved.

LUBREX

https://www.lubrex.com.tr/

lubrex@lubrex.com.tr